




## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** KMK 4425 NORM HARD. (FOR 27\_2805)  
**Other means of identification:**  
**UFI:** AY00-F0VA-Y000-34FH
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Hardener for coatings. For professional users/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
Kimakem srl  
Via Don G. Fortuna 82  
36050 Monteviale - Vicenza - Italia  
Phone: +39 0444 1220020  
info@kimakem.com
- 1.4 Emergency telephone number:** +39 0444 1220020 (Monday to Friday 8:30 -17:30 GMT +1:00)

## SECTION 2: HAZARDS IDENTIFICATION \*\*

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336  
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Danger**  

- Hazard statements:**  
H225 - Highly flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H412 - Harmful to aquatic life with long lasting effects.
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH204: Contains isocyanates. May produce an allergic reaction.
- Substances that contribute to the classification**  
Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O); N-butyl acetate; Ethyl acetate; Hydrocarbons, C9, aromatics
- UFI:** AY00-F0VA-Y000-34FH

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)**

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product does not meet the criteria.

\*\* Changes with regards to the previous version

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**







Non-applicable

**3.2 Mixture:**

**Chemical description:** polyisocyanate

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification  | Chemical name/Classification  |   | Concentration |
|---|---|---|---------------|
| CAS: 28182-81-2<br>EC: 931-274-8<br>Index: Non-applicable<br>REACH: 01-2119485796-17-XXXX | Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O) <sup>(1)</sup>                                       | Self-classified   | 50 - <75 %    |
| Regulation 1272/2008  | Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning   |    |               |
| CAS: 123-86-4<br>EC: 204-658-1<br>Index: 607-025-00-1<br>REACH: 01-2119485493-29-XXXX     | N-butyl acetate <sup>(1)</sup>  | ATP CLP00   | 25 - <50 %    |
| Regulation 1272/2008  | Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning   |    |               |
| CAS: 141-78-6<br>EC: 205-500-4<br>Index: 607-022-00-5<br>REACH: 01-2119475103-46-XXXX     | Ethyl acetate <sup>(1)</sup>  | ATP CLP00   | 5 - <10 %     |
| Regulation 1272/2008  | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger  |    |               |
| CAS: 64742-95-6<br>EC: Non-applicable<br>Index: Non-applicable<br>REACH: Non-applicable   | Hydrocarbons, C9, aromatics <sup>(1)</sup>  | Self-classified   | 2,5 - <5 %    |
| Regulation 1272/2008  | Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger | <br><br> |               |

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification   | Acute toxicity  |                | Genus |
|--|-----------------|----------------|-------|
|  | LD50 oral       | Not relevant   |       |
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2<br>EC: 931-274-8 | LD50 oral       | Not relevant   |       |
|  | LD50 dermal     | Not relevant   |       |
|  | LC50 inhalation | 11 mg/L (ATEI) |       |

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

- CONTINUED ON NEXT PAGE -



#### SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not relevant

#### SECTION 5: FIREFIGHTING MEASURES

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -



**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification                                 | Occupational exposure limits |         |                        |
|--|------------------------------|---------|------------------------|
|  | IOELV (8h)                   | 50 ppm  | 241 mg/m <sup>3</sup>  |
| N-butyl acetate<br>CAS: 123-86-4 EC: 204-658-1 | IOELV (STEL)                 | 150 ppm | 723 mg/m <sup>3</sup>  |
| Ethyl acetate<br>CAS: 141-78-6 EC: 205-500-4   | IOELV (8h)                   | 200 ppm | 734 mg/m <sup>3</sup>  |
|  | IOELV (STEL)                 | 400 ppm | 1468 mg/m <sup>3</sup> |

**DNEL (Workers):**

| Identification   |            | Short exposure        |                       | Long exposure         |                       |
|--|------------|-----------------------|-----------------------|-----------------------|-----------------------|
|  |            | Systemic              | Local                 | Systemic              | Local                 |
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2<br>EC: 931-274-8 | Oral       | Not relevant          | Not relevant          | Not relevant          | Not relevant          |
|  | Dermal     | Not relevant          | Not relevant          | Not relevant          | Not relevant          |
|  | Inhalation | Not relevant          | 1 mg/m <sup>3</sup>   | Not relevant          | 0,5 mg/m <sup>3</sup> |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1  | Oral       | Not relevant          | Not relevant          | Not relevant          | Not relevant          |
|  | Dermal     | 11 mg/kg              | Not relevant          | 11 mg/kg              | Not relevant          |
|  | Inhalation | 600 mg/m <sup>3</sup> | 600 mg/m <sup>3</sup> | 300 mg/m <sup>3</sup> | 300 mg/m <sup>3</sup> |

- CONTINUED ON NEXT PAGE -



**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Identification   |            | Short exposure         |                        | Long exposure         |                       |
|--|------------|------------------------|------------------------|-----------------------|-----------------------|
|  |            | Systemic               | Local                  | Systemic              | Local                 |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4                      | Oral       | Not relevant           | Not relevant           | Not relevant          | Not relevant          |
|  | Dermal     | Not relevant           | Not relevant           | 63 mg/kg              | Not relevant          |
|  | Inhalation | 1468 mg/m <sup>3</sup> | 1468 mg/m <sup>3</sup> | 734 mg/m <sup>3</sup> | 734 mg/m <sup>3</sup> |
| Hydrocarbons, C9, aromatics<br>CAS: 64742-95-6<br>EC: Non-applicable | Oral       | Not relevant           | Not relevant           | Not relevant          | Not relevant          |
|  | Dermal     | Not relevant           | Not relevant           | 25 mg/kg              | Not relevant          |
|  | Inhalation | Not relevant           | Not relevant           | 150 mg/m <sup>3</sup> | Not relevant          |

**DNEL (General population):**

| Identification   |            | Short exposure        |                       | Long exposure          |                        |
|--|------------|-----------------------|-----------------------|------------------------|------------------------|
|  |            | Systemic              | Local                 | Systemic               | Local                  |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1                    | Oral       | 2 mg/kg               | Not relevant          | 2 mg/kg                | Not relevant           |
|  | Dermal     | 6 mg/kg               | Not relevant          | 6 mg/kg                | Not relevant           |
|  | Inhalation | 300 mg/m <sup>3</sup> | 300 mg/m <sup>3</sup> | 35,7 mg/m <sup>3</sup> | 35,7 mg/m <sup>3</sup> |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4                      | Oral       | Not relevant          | Not relevant          | 4,5 mg/kg              | Not relevant           |
|  | Dermal     | Not relevant          | Not relevant          | 37 mg/kg               | Not relevant           |
|  | Inhalation | 734 mg/m <sup>3</sup> | 734 mg/m <sup>3</sup> | 367 mg/m <sup>3</sup>  | 367 mg/m <sup>3</sup>  |
| Hydrocarbons, C9, aromatics<br>CAS: 64742-95-6<br>EC: Non-applicable | Oral       | Not relevant          | Not relevant          | 11 mg/kg               | Not relevant           |
|  | Dermal     | Not relevant          | Not relevant          | 11 mg/kg               | Not relevant           |
|  | Inhalation | Not relevant          | Not relevant          | 32 mg/m <sup>3</sup>   | Not relevant           |

**PNEC:**



| Identification   |              |              |                         |              |
|--|--------------|--------------|-------------------------|--------------|
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2<br>EC: 931-274-8 | STP          | 88 mg/L      | Fresh water             | 0,127 mg/L   |
|  | Soil         | 53183 mg/kg  | Marine water            | 0,013 mg/L   |
|  | Intermittent | 1,27 mg/L    | Sediment (Fresh water)  | 266701 mg/kg |
|  | Oral         | Not relevant | Sediment (Marine water) | 26670 mg/kg  |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1  | STP          | 35,6 mg/L    | Fresh water             | 0,18 mg/L    |
|  | Soil         | 0,09 mg/kg   | Marine water            | 0,018 mg/L   |
|  | Intermittent | 0,36 mg/L    | Sediment (Fresh water)  | 0,981 mg/kg  |
|  | Oral         | Not relevant | Sediment (Marine water) | 0,098 mg/kg  |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4  | STP          | 650 mg/L     | Fresh water             | 0,24 mg/L    |
|  | Soil         | 0,148 mg/kg  | Marine water            | 0,024 mg/L   |
|  | Intermittent | 1,65 mg/L    | Sediment (Fresh water)  | 1,15 mg/kg   |
|  | Oral         | 0,2 g/kg     | Sediment (Marine water) | 0,115 mg/kg  |

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram   | PPE                               | Labelling   | CEN Standard        | Remarks  |
|---|-----------------------------------|---|---------------------|--|
| <br>Mandatory respiratory tract protection | Filter mask for gases and vapours |  | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |



C.- Specific protection for the hands

- CONTINUED ON NEXT PAGE -





**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**





| Pictogram  | PPE   | Labelling   | CEN Standard      | Remarks  |
|--|---|---|-------------------|--|
| <br>Mandatory hand protection | Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) |  | EN ISO 21420:2020 | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

| Pictogram  | PPE         | Labelling   | CEN Standard  | Remarks   |
|--|-------------|---|---|---|
| <br>Mandatory face protection | Face shield |  | EN 166:2002<br>EN 167:2002<br>EN 168:2002<br>EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram   | PPE   | Labelling   | CEN Standard  | Remarks   |
|---|---|---|---|---|
| <br>Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |    | EN 1149-1,2,3<br>EN 13034:2005+A1:2009<br>EN ISO 13982-1:2004/A1:2010<br>EN ISO 6529:2013<br>EN ISO 6530:2005<br>EN ISO 13688:2013<br>EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| <br>Mandatory foot protection        | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN ISO 13287:2020<br>EN ISO 20345:2011<br>EN 13832-1:2019   | Replace boots at any sign of deterioration.   |

F.- Additional emergency measures

| Emergency measure   | Standards                                       | Emergency measure  | Standards                                      |
|---|---|--|--|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

|                           |                                 |
|---------------------------|---------------------------------|
| V.O.C. (Supply):          | 44,5 % weight                   |
| V.O.C. density at 20 °C:  | 444 kg/m <sup>3</sup> (444 g/L) |
| Average carbon number:    | 5,98                            |
| Average molecular weight: | 113,33 g/mol                    |

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

|                          |            |
|--------------------------|------------|
| Physical state at 20 °C: | Liquid     |
| Appearance:              | Fluid      |
| Colour:                  | Colourless |

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

|  |                            |
|--|----------------------------|
| Odour:                                       | Characteristic             |
| Odour threshold:                             | Not relevant *             |
| <b>Volatility:</b>                           |                            |
| Boiling point at atmospheric pressure:       | 77 - 255 °C                |
| Vapour pressure at 20 °C:                    | 2433 Pa                    |
| Vapour pressure at 50 °C:                    | 10378,23 Pa (10,38 kPa)    |
| Evaporation rate at 20 °C:                   | Not relevant *             |
| <b>Product description:</b>                  |                            |
| Density at 20 °C:                            | 1021 kg/m <sup>3</sup>     |
| Relative density at 20 °C:                   | 1                          |
| Dynamic viscosity at 20 °C:                  | 80 cP                      |
| Kinematic viscosity at 20 °C:                | 2990,55 mm <sup>2</sup> /s |
| Kinematic viscosity at 40 °C:                | >20,5 mm <sup>2</sup> /s   |
| Concentration:                               | Not relevant *             |
| pH:  | Not relevant *             |
| Vapour density at 20 °C:                     | Not relevant *             |
| Partition coefficient n-octanol/water 20 °C: | Not relevant *             |
| Solubility in water at 20 °C:                | Not relevant *             |
| Solubility properties:                       | Immiscible                 |
| Decomposition temperature:                   | Not relevant *             |
| Melting point/freezing point:                | Not relevant *             |
| <b>Flammability:</b>                         |                            |
| Flash Point:                                 | 21 °C                      |
| Flammability (solid, gas):                   | Not relevant *             |
| Autoignition temperature:                    | 421 °C                     |
| Lower flammability limit:                    | Not available              |
| Upper flammability limit:                    | Not available              |
| <b>Particle characteristics:</b>             |                            |
| Median equivalent diameter:                  | Non-applicable             |

### 9.2 Other information:

#### Information with regard to physical hazard classes:

|  |                |
|--|----------------|
| Explosive properties:  | Not relevant * |
| Oxidising properties:  | Not relevant * |
| Corrosive to metals:   | Not relevant * |
| Heat of combustion:  | Not relevant * |
| Aerosols-total percentage (by mass) of flammable components: | Not relevant * |

#### Other safety characteristics:

|                           |                |
|---------------------------|----------------|
| Surface tension at 20 °C: | Not relevant * |
| Refraction index:         | Not relevant * |

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

- CONTINUED ON NEXT PAGE -



**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 10: STABILITY AND REACTIVITY (continued)**

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight            | Humidity       |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable     | Not applicable   | Risk of combustion      | Avoid direct impact | Not applicable |

**10.5 Incompatible materials:**

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Hydrocarbons, C9, aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- CONTINUED ON NEXT PAGE -





**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

| Identification   | Acute toxicity  |                 | Genus  |
|--|-----------------|-----------------|--------|
|  | Route           | Value           |        |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1  | LD50 oral       | 12789 mg/kg     | Rat    |
|  | LD50 dermal     | 14112 mg/kg     | Rabbit |
|  | LC50 inhalation | 23,4 mg/L (4 h) | Rat    |
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2<br>EC: 931-274-8 | LD50 oral       | 2660 mg/kg      | Rat    |
|  | LD50 dermal     | >2000 mg/kg     |        |
|  | LC50 inhalation | 11 mg/L (ATEi)  |        |
| Hydrocarbons, C9, aromatics<br>CAS: 64742-95-6<br>EC: Non-applicable                             | LD50 oral       | >2000 mg/kg     |        |
|  | LD50 dermal     | >2000 mg/kg     |        |
|  | LC50 inhalation | >20 mg/L        |        |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4  | LD50 oral       | 4100 mg/kg      | Rat    |
|  | LD50 dermal     | 20000 mg/kg     | Rabbit |
|  | LC50 inhalation | >20 mg/L        |        |

**11.2 Information on other hazards:**

**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Not relevant

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

**12.1 Toxicity:**

**Acute toxicity:**

| Identification   | Concentration |                     | Species                 | Genus      |
|--|---------------|---------------------|-------------------------|------------|
|  | Route         | Value               |                         |            |
| Hexamethylene diisocyanate, oligomers (<0.1 % O=C=N-R-N=C=O)<br>CAS: 28182-81-2<br>EC: 931-274-8 | LC50          | Not relevant        |                         |            |
|  | EC50          | Not relevant        |                         |            |
|  | EC50          | 1000 mg/L (72 h)    | Scenedesmus subspicatus | Algae      |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1  | LC50          | Not relevant        |                         |            |
|  | EC50          | Not relevant        |                         |            |
|  | EC50          | 675 mg/L (72 h)     | Scenedesmus subspicatus | Algae      |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4  | LC50          | 230 mg/L (96 h)     | Pimephales promelas     | Fish       |
|  | EC50          | 717 mg/L (48 h)     | Daphnia magna           | Crustacean |
|  | EC50          | 3300 mg/L (48 h)    | Scenedesmus subspicatus | Algae      |
| Hydrocarbons, C9, aromatics<br>CAS: 64742-95-6<br>EC: Non-applicable                             | LC50          | >1 - 10 mg/L (96 h) |                         | Fish       |
|  | EC50          | >1 - 10 mg/L (48 h) |                         | Crustacean |
|  | EC50          | >1 - 10 mg/L (72 h) |                         | Algae      |

**Chronic toxicity:**

- CONTINUED ON NEXT PAGE -



**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

| Identification                                 | Concentration |              | Species             | Genus      |
|--|---------------|--------------|---------------------|------------|
|  | NOEC          | Not relevant |                     |            |
| N-butyl acetate<br>CAS: 123-86-4 EC: 204-658-1 | NOEC          | 23,2 mg/L    | Daphnia magna       | Crustacean |
| Ethyl acetate<br>CAS: 141-78-6 EC: 205-500-4   | NOEC          | 9,65 mg/L    | Pimephales promelas | Fish       |
|  | NOEC          | 2,4 mg/L     | Daphnia magna       | Crustacean |

**12.2 Persistence and degradability:**

**Substance-specific information:**

| Identification                                    | Degradability |              | Biodegradability |              |
|---|---------------|--------------|------------------|--------------|
|   | BOD5          | Not relevant | Concentration    | Not relevant |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1 | COD           | Not relevant | Period           | 5 days       |
|   | BOD5/COD      | Not relevant | % Biodegradable  | 84 %         |
|   | BOD5          | 1,36 g O2/g  | Concentration    | 100 mg/L     |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4   | COD           | 1,69 g O2/g  | Period           | 14 days      |
|   | BOD5/COD      | 0,8          | % Biodegradable  | 83 %         |

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

| Identification                                    | Bioaccumulation potential |             |
|---|---------------------------|-------------|
|   | BCF                       | 4           |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1 | Pow Log                   | 1.78        |
|   | Potential                 | Low         |
|   | BOD5                      | 1,36 g O2/g |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4   | Pow Log                   | 0.73        |
|   | Potential                 | Moderate    |

**12.4 Mobility in soil:**

| Identification                                    | Absorption/desorption |                      | Volatility    |              |
|---|-----------------------|----------------------|---------------|--------------|
|   | Koc                   | Not relevant         | Henry         | Not relevant |
| N-butyl acetate<br>CAS: 123-86-4<br>EC: 204-658-1 | Conclusion            | Not relevant         | Dry soil      | Not relevant |
|   | Surface tension       | 2,478E-2 N/m (25 °C) | Moist soil    | Not relevant |
|   | BOD5                  | 1,36 g O2/g          | Concentration | 100 mg/L     |
| Ethyl acetate<br>CAS: 141-78-6<br>EC: 205-500-4   | Conclusion            | Very High            | Dry soil      | Yes          |
|   | Surface tension       | 2,324E-2 N/m (25 °C) | Moist soil    | Yes          |

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

| Code      | Description   | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Hazardous                                  |

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

- CONTINUED ON NEXT PAGE -



**KMK 4425 NORM HARD. (FOR 27\_2805)**

**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Special regulations: 163, 367, 650  
Tunnel restriction code: D/E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by sea:**

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 163, 223, 955, 367  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2024:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT RELATED MATERIAL
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

- CONTINUED ON NEXT PAGE -



## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

#### Seveso III:

| Section | Description       | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c     | FLAMMABLE LIQUIDS | 5000                    | 50000                   |

#### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

#### Texts of the legislative phrases mentioned in section 2:

- H336: May cause drowsiness or dizziness.
- H335: May cause respiratory irritation.
- H317: May cause an allergic skin reaction.
- H412: Harmful to aquatic life with long lasting effects.
- H225: Highly flammable liquid and vapour.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

- Acute Tox. 4: H332 - Harmful if inhaled.
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- STOT SE 3: H335 - May cause respiratory irritation.
- STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

- CONTINUED ON NEXT PAGE -



**SECTION 16: OTHER INFORMATION (continued)**

STOT SE 3: Calculation method  
STOT SE 3: Calculation method  
Skin Sens. 1: Calculation method  
Aquatic Chronic 3: Calculation method  
Flam. Liq. 2: Calculation method (2.6.4.3)

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -